

Terminal Tractor/Yard Spotter

Used Yard Spotter Delaware - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. Tow tractors are responsible for moving multiple trailers in a train. Some are designed specifically to tow large aircraft in order to position them into and out of airport terminals and hangers. Tractive effort is how these machines transport loads. Tractive effort is the amount of traction a unit has on the ground. Heavier loads require more tractive effort compared to lighter loads. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. Traction allows the machine to deliver very large and heavy loads. Types of Tow Tractors There are two basic types of tow tractors: 1. Load carriers; and 2. Heavy-duty tow tractors; Load Carriers Industries such as e-commerce, manufacturing, and airport baggage and parcel systems must regularly move many individual and varying sized items to or from a single location. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. The category that load carrier tow tractor models fall into includes forklift trucks, cranes and pallet jacks. Load carrier tow tugs transport loads at ground level only, rather than lifting or lowering off the ground or from shelving or other hard to reach areas. In order to be ready for transport, items must be secured on a wheeled platform or already on wheels to use the tow tractor. The wheeled platforms are called bogies, trollies or skates. The tow tractor joins to the trolly and functions similarly to a train locomotive. Usually, the tow tug has a male-end steel coupling that couples to the femaleend fixed to the front of the trolly. Trollies move in a train-like system thanks to the male-end steel coupling on the back which can connect to numerous units and allow a single tug to transport them. Tow tractors with a train of trollies enable a wider range in the type of items that can be transported and in the types of conditions they can be transported. Trolly types differ to provide customization options. Many trollies can be connected since they are compatible with one another. Different kinds of trollies can be maneuvered in a single train, creating flexible transport options. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. This is vital for safety-sensitive places including airports and manufacturing facilities. Towing solutions are a good alternative to traditional forklifts to handle many single items. Tugs are easy to move and safe to use. The operator doesn't require a license, which is another benefit compared to forklifts. Tow tractor operators do not need licenses since they don't lift loads off of the ground. There are three subtypes of load carrier tow tractors: 1. Pedestrian; 2. Stand-in; and 3. Rider-seated. Pedestrian Tow Tractors A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. These machines are simple to use, extremely maneuverable and very compact. Stand-in Tow Tractors The most common design for businesses that rely on horizontal manufacturing transport and order picking are stand-in tow tractors. These units deliver a secure driver platform and deliver a smaller footprint compared to the rider-seated models. Rider-Seated Tow Tractors Similar to stand-in tow tractors, rider-seated units have a seated operator platform. Riderseated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. Rider fatigue is decreased with sit-down units for more efficiency and productivity. Heavy Duty Tow Tractors Aviation relies on the pushback concept for moving big passenger and cargo aircraft. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. Pushback is achieved by employing pushback tugs or pushback tractors. Pushback tractors are designed with

a low profile design to enable them to move under the aircraft's nose in order to attach to the aircraft. Because of the added heavy weight of the aircraft, these tow tractors must be heavy enough to retain enough traction on the ground in order to move the aircraft. A typical tractor for large aircraft weighs up to 54 tons. They usually have a driver's cab that can be raised and lowered to increase visibility when reversing. The pushback tow tractor and pushback tug are also employed when taxiing the aircraft is not an option. They are commonly used to move the machine into and outside of aircraft maintenance hangars. There are two subtypes of pushback tow tractors: 1. Conventional; and 2. Towbarless. Conventional Pushback Tow Tractors Conventional units rely on a tow bar to connect the tug to the aircraft's nose landing gear. Laterally attached to the nose landing gear, the tow tractor can make certain slight vertical height adjustments if needed. The tow bar is able to pivot vertically and laterally at the end that connects to the tug. The tow bar functions as a sizeable lever to facilitate nose landing gear rotation. Each aircraft type has a unique tow fitting so the towbar also acts as an adapter between the standard-sized tow pin on the tug and the typespecific fitting on the aircraft's landing gear. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled. Towbarless Pushback Tow Tractors Towbarless tractors work without a towbar and scoop up the aircrafts' nose landing gear to lift it off of the ground instead. This design facilitates higher speeds greater aircraft control and can eliminate the necessity of having a worker inside of the cockpit to apply the brakes. The main advantage of a towbarless tug is simplicity; there is no need to maintain multiple towbars. Directly connecting the tug to the landing gear allows operators to have better responsiveness and control while moving the aircraft.